









# Supported devices for The Observer XT - stationary set-up

The table below shows the maximum supported (1) resolution, (2) frame rate (fps), (3) number of devices and (4) recording time (hours). Tests were done on a Dell Precision T3620 PC

	Device	Resolution	Frame rate	Number of devices	Recording time
	Axis M5525 (separate videos, line-in audio and camera audio*)	1920 x 1080	25 30	4	3
	Axis M5525 (Picture-by-picture & Picture-in-picture, line-in audio)	1920 x 1080	30	4	3
	Axis M5054	1280 x 720	30	1	3
	Axis M1065-L (separate videos, line-in audio and camera audio)	1920 x 1080	25	4	2
	Axis M5525 + M1065-L (separate videos, line-in audio and camera audio)	1920 x 1080	30	2+2	3
	Axis M5525 + Epiphan Pearl Nano (separate videos, line-in audio and camera audio (broadcaster no audio))	1920 x 1080	25	3+1	3
	Axis M1065-L + Epiphan Pearl Nano (do NOT use Picture-in-picture or picture-by-picture)	1920 x 1080	30	3+1	2

	Axis M5525 + M1065-L + Epiphan Pearl Nano (separate videos, line-in audio and camera audio (no audio broadcaster))	1920 x 1080	30	1+2+1	3
---	--	-------------	----	-------	---

\* Camera audio = audio over RTSP

Revision #3  
Created 1 December 2023 10:33:52  
Updated 2 January 2024 20:51:32