

# Supported devices

## Tested devices

The latest version of MediaRecorder has extensively been tested with the following devices:

### IP cameras

- Axis P1375
- Axis M5525
- Axis M1075-L

### Screen capture devices

- Epiphan Pearl Nano

## Earlier versions of MediaRecorder have been tested with the following devices:

### Analog cameras

PhenoTyper Top Unit camera (EIA and CCIR) in combination with

- the Euresys Picolo Alert PCIe

### IP cameras

- Axis P5512
- Axis P5514
- Axis P5515
- Axis P5534
- Axis M1054
- Axis M1065-L
- Hikvision IP DS-2PT7D20IW-DE

### USB cameras

- Basler acA1920-155um USB 3.0 camera
- Basler acA2040-90uc
- Logitech BRIO USB 3.0 camera

### FireWire camera

- The Imaging Source DMK 21AF04 for the DanioVision system with FireWire camera.

## GigE camera

- Basler acA1300-60gm monochrome camera.

## Screen capture devices

- Epiphan DVI2USB 3.0.
- Epiphan VGADVI broadcaster.
- The MR Screen Capture Module.

## Combinations of devices

- Portable Observation Lab version 6 (two Logitech BRIO USB 3.0 cameras).
- Portable Observation Lab version 5 (two Axis M1065 IP cameras).
- Portable Usability Lab version 5 (one Logitech BRIO USB 3.0 camera and one Epiphan DVI2USB 3.0 screen capture device).
- Stationary Usability Lab (three IP cameras and one Epiphan VGADVI broadcaster).

## Keyboard

CH products RS Desktop joystick for Pan, Tilt, and Zoom control of IP cameras.

---

Revision #12

Created 29 November 2023 16:57:04

Updated 20 December 2023 22:16:57